

Single door - sash lock

1

Hardware set data sheet

Overhead door closing device with backcheck only

ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.

Mortice sashlock case

ESD910



- Function: Latch bolt and deadbolt operation.
- Deadbolt projection: 21mm, single throw.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Din lock intumescent pack

ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

Stainless steel lever handle set on rose for interior doors

ESD - E138F/42K-A2



- Material: Stainless steel grade 304.
- Bearing: Fixed/movable.
- Connection: Solid spindle with eccentric hole on both ends.
- Base: Stainless steel.
- Fixing: Bolt through and wood screws.

70mm Euro profile thumbturn cylinder

ESD312170T



- Cylinder type: Key and turn cylinder.
- Keying function: Keyed to differ.
- Number of keys: 2 servant keys.

Escutcheon

ESD - ESC/TURN



- Euro profile escutcheon 8mm.
- Fixing: 4 x 20mm screws.
- Material: Grade 304 stainless steel.

Fire door keep shut sign

ESD902



- With lettering.
- 76mm diameter.
- Qty: 2.

Single door - dead lock

2

Hardware set data sheet

Overhead door closing device with backcheck only ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.

Escutcheon ESD - ESC/TURN



- Euro profile escutcheon 8mm.
- Fixing: 4 x 20mm screws.
- Material: Grade 304 stainless steel.

Mortice deadlock case ESD912



- Function: Deadbolt operation.
- Deadbolt projection: 21mm, single throw.
- Forend/strike material: Stainless steel.
- Forend type: Single.

300mm Stainless steel straight pull handle (exterior side) ESD3616-300



- Fixing: Pull handle fixing system no.BS13-B.

Din lock intumescent pack ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

350mm Finger plate with radius corners ESD324-300



- Material: Stainless steel grade 304.
- Fixing: Drilled and countersunk supplied with wood screws.
- Radius corner.

70mm Euro profile thumbturn cylinder ESD312170T



- Cylinder type: Key and turn cylinder.
- Keying function: Keyed to differ.
- Number of keys: 2 servant keys.

Fire door keep locked sign ESD901



- With lettering.
- 76mm diameter.
- Qty: 2.

Single door - latch only

3

Hardware set data sheet

Overhead door closing device with backcheck only

ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.

Mortice latch case

ESD911



- Function: Latch bolt operation.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Din lock intumescent pack

ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

Stainless steel lever handle set on rose for interior doors

ESD - E138F/42K-A2



- Material: Stainless steel grade 304.
- Bearing: Fixed/movable.
- Connection: Solid spindle with eccentric hole on both ends.
- Base: Stainless steel.
- Fixing: Bolt through and wood screws.

Fire door keep shut sign

ESD902



- With lettering.
- 76mm diameter.
- Qty: 2.

Single door - bathroom

4

Hardware set data sheet

Overhead door closing device with backcheck only

ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.

Mortice bathroom lock

ESD913



- Function: Latch bolt and deadbolt operation.
- Deadbolt projection: 21mm, single throw.
- 8mm bathroom follower with 5mm adaptor supplied.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Din lock intumescent pack

ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

Stainless steel lever handle set on rose for interior doors

ESD - E138F/42K-A2



- Material: Stainless steel grade 304.
- Bearing: Fixed/movable.
- Connection: Solid spindle with eccentric hole on both ends.
- Base: Stainless steel.
- Fixing: Bolt through and wood screws.

Bathroom turn and indicator set

ESD - IND/TURN



- Function: Bathroom turn set for residential/commercial applications.
- Material: Stainless steel grade 304.
- Base: Stainless steel.
- Fixing: Wood screws with 5mm bathroom spindle.

Fire door keep shut sign

ESD902



- With lettering.
- 76mm diameter.
- Qty: 2.

Single door - non locking

5

Hardware set data sheet

Overhead door closing device with backcheck only

ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.

300mm Stainless steel straight pull handle (exterior side)

ESD616-300



- Fixing: Pull handle fixing system no. BS13-B.

350mm Finger plate with radius corners

ESD324-300



- Material: Stainless steel grade 304.
- Fixing: Drilled and countersunk supplied with wood screws.
- Radius corner.

Fire door keep shut sign

ESD902



- With lettering.
- 76mm diameter.
- Qty: 2.

Double door - sash lock

6

Hardware set data sheet

Overhead door closing device with backcheck only ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.
- Qty: 2.

Escutcheon ESD - ESC/TURN



- Euro profile escutcheon 8mm.
- Fixing: 4 x 20mm screws.
- Material: Grade 304 stainless steel.

Mortice sashlock case ESD910



- Function: Latch bolt and deadbolt operation.
- Deadbolt projection: 21mm, single throw.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Stainless steel lever handle ESD - E138F/42K-A2 set on rose for interior doors



- Material: Stainless steel grade 304.
- Bearing: Fixed/movable.
- Connection: Solid spindle with eccentric hole on both ends.
- Base: Stainless steel.
- Fixing: Bolt through and wood screws.

Din lock intumescent pack ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

Flush bolt ESD326



- Material: Stainless steel.
- Function: Lever action.
- Fixing: Timber door screws.
- Qty 2 - (please note only 1 supplied if drop seals are in use)
- Fire rated products to be supplied with intumescents.

70mm Euro profile thumbturn cylinder ESD312170T



- Cylinder type: Key and turn cylinder.
- Keying function: Keyed to differ.
- Number of keys: 2 servant keys.

Fire door keep shut sign ESD902



- With lettering.
- 76mm diameter.
- Qty: 4.

Double door - dead lock

7

Hardware set data sheet

Overhead door closing device with backcheck only ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.
- Qty: 2.

Mortice deadlock case ESD912



- Function: Deadbolt operation.
- Deadbolt projection: 21mm, single throw.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Din lock intumescent pack ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

70mm Euro profile thumbturn cylinder ESD312170T



- Cylinder type: Key and turn cylinder.
- Keying function: Keyed to differ.
- Number of keys: 2 servant keys.

Escutcheon ESD - ESC/TURN



- Euro profile escutcheon 8mm.
- Fixing: 4 x 20mm screws.
- Material: Grade 304 stainless steel.

300mm Stainless steel straight pull handle (exterior side) ESD3616-300



- Fixing: Pull handle fixing system no. BS13-B.
- Qty: 2.

350mm Finger plate with radius corners ESD324-300



- Material: Stainless steel grade 304.
- Fixing: Drilled and countersunk supplied with wood screws.
- Radius corner.
- Qty: 2.

Flush bolt ESD326



- Material: Stainless steel.
- Function: Lever action.
- Fixing: Timber door screws.
- Qty 2 - (please note only 1 supplied if drop seals are in use).
- Fire rated products to be supplied with intumescents.

Fire door keep locked sign ESD901



- With lettering.
- 76mm diameter.
- Qty: 4.

Double door - latch only

8

Hardware set data sheet

Overhead door closing device with backcheck only

ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.
- Qty: 2.

Mortice latch case

ESD911



- Function: Latch bolt operation.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Din lock intumescent pack

ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

Stainless steel lever handle set on rose for interior doors

ESD - E138F/42K-A2



- Material: Stainless steel grade 304.
- Bearing: Fixed/movable.
- Connection: Solid spindle with eccentric hole on both ends.
- Base: Stainless steel.
- Fixing: Bolt through and wood screws.

Flush bolt

ESD326



- Material: Stainless steel.
- Function: Lever action.
- Fixing: Timber door screws.
- Qty 2 - (please note only 1 supplied if drop seals are in use).
- Fire rated products to be supplied with intumescents.

Fire door keep shut sign

ESD902



- With lettering.
- 76mm diameter.
- Qty: 4.

Double door - non locking

9

Hardware set data sheet

Overhead door closing device with backcheck only

ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.
- Qty: 2.

300mm Stainless steel straight pull handle (exterior side)

ESD3616-300



- Fixing: Pull handle fixing system no. BS13-B.
- Qty: 2.

350mm Finger plate with radius corners

ESD324-300



- Material: Stainless steel grade 304.
- Fixing: Drilled and countersunk supplied with wood screws.
- Radius corner.
- Qty: 2.

Fire door keep shut sign

ESD902



- With lettering.
- 76mm diameter.
- Qty: 4.